

TECHNICAL DATA SHEET

PP Matte Aluminium

Product name:

Film customised with the client's branding, and produced in rolls or in pouches:

- Stand-up pouches/Doypacks
- Flat pouches
- Rolls of different lengths with an internal plastic core
(min 50 mm – max 750 mm)

At the customer's request, the following can be added to the stand-up pouches/Doypacks and flat pouches:


- Plastic (PP) aroma protection/pressure relief valve for ground coffee or coffee beans
- Plastic zip fastening (PP)
- Hole/euro slot
- Spout (PP)

Constituent materials:

Laminated aluminium and plastic film (PP inside)

Composition of multi-layer film – BOPP + Aluminium + PP CAST:

COMPONENTS	VALUES
BOPP	12 ± 5 % µm
EVA	8 ± 5 % µm
AL	9 ± 5 % µm
Adhesive	2 ± 5 % g
PP CAST	80 ± 5 % µm
TOTAL THICKNESS	109 ± 5 % µm



Solvent-less Adhesive

*The thickness and weight of the ink vary depending on the customer's artwork.

Physical and chemical properties:

PROPERTY	METHOD	UNIT	VALUE (BONDED MATERIAL)
GRAMMAGE	In-house method	g/m ²	115,40
INITIAL BONDING TEMPERATURE	In-house method	°C x sec	180-190 x 0.20-0.30
WATER VAPOUR PERMEABILITY	ASTM F1249-06	g/m2x24h _{xatm} 38°C – 90% RH	< 0,05
OXYGEN PERMEABILITY	ASTM F2622-08	cc/m2x24h _{xatm} 23°C – 0% RH	< 0,05
CO2 PERMEABILITY	ASTM F2476-05	cc/m2x24h _{xatm} 23°C – 0% RH	1,8

The values have a tolerance of +/- 5%

General conditions of use:

Flexible packaging suitable for contact with food.

(See declaration of compliance for food contact materials supplied with the product, under general conditions of use).



Recoverable plastic packaging to be collected separately and disposed of following local guidelines.

PLASTIC
PACKAGING



C/PP 90
Follow the guidelines
of local waste disposal regulations

Storage:

- Store the product in a dry, protected, clean place and in closed packages to prevent contamination.
- Store out of direct sunlight and at a temperature not exceeding 30°C and not less than 15°C.

Filling:

- Filling capacities are given on the website in the "MARKETS" section (www.packstyle.com).
- Despite the values reported on the site, it is recommended not to fill the pouches beyond 2/3 of their capacity.
- Allow air to exit before closing and sealing

Transport:

- Pack your product carefully. We recommend the use of shock-protective material on the bottom of boxes and sides of envelopes (e.g., bubble wrap or air cushions)

Forms of packaging and/or protection:

Packaging:

Pouches: Plastic cable ties (PP)

Packing:

Pouches: Cardboard box + plastic air cushions (LDPE)

Rolls: Wooden pallet + extensible film (LLDPE) or cardboard box + plastic air cushions (LDPE)

Applicable framework laws:

Food contact safety and compliance:

Regulation (EC) 1935/04 s.m.i.

Regulation (EC) 2023/06 s.m.i.

Regulation (EU) 10/2011 s.m.i.

Italian Presidential Decree 777/1982 s.m.i.

Ministerial Decree of 21 March 1973 s.m.i.

Environmental compliance:

Directive 94/62/EC s.m.i.

Italian Legislative Decree 152/2006 s.m.i.